

ALTHEA06W 2-Port USB-A Charger 12W

Product Images



Short Description

- **Dedicated Port Connector:** Equipped with 2 USB-A ports, each providing DC 5.0V/2.4A, offering up to 12.0W of total power and high-speed charging for a wide range of devices

with varying power requirement.

- **Enhanced Safety Features:** Built-in protections against overload, short circuiting, and overheating, ensuring the safety of both the charger and connected devices.

Description

Equipped with 2 USB-A ports, each providing DC 5.0V/2.4A, this charger offers up to 12.0W of total power for high-speed charging across a wide range of devices with varying power requirements. Enhanced safety features include built-in protections against overload, short-circuiting, and overheating, ensuring the safety of both the charger and the connected devices.

Additional Information

Number of cartons per pallet.	36 piece
Pallet Net Depth.	700 millimeter
Pallet Net Width.	1200 millimeter
Pallet Net Height.	1752 millimeter
Power Plug Type.	EU
Number of simultaneously connected devices (max).	2
Port 2 Power Output.	DC 5.0V/2.4A
Port 1 Power Output.	DC 5.0V/2.4A
Programmable power supply (PPS) (YES/NO).	No
USB Type-A ports quantity.	2
Number of outputs.	2
Housing Material.	Polycarbonate (PC)
Harmonized System (HS) code.	8504408390
Customs product code (TARIC).	8504408390
Quantity per Pallet.	3600 piece
Input current.	0.5 ampere
Maximum AC Input.	240 volt
Minimum AC Input.	100 volt
Maximum power.	12 watt
Power Protection Features.	Over current, Over power, Short circuit
Sustainability Compliance.	No
Approval and Compliance.	CE, RoHS
Package Content.	Quick installation guide
Operating humidity.	20% RH ~ 80% RH
Operating temperature.	0°C ~ 40°C

Storage humidity.	10% RH ~ 90% RH
Storage temperature.	-20°C ~ 80°C
Package Contents.	ALTHEA06W Multilingual quick installation guide
Color.	White
EAN.	4015867240687
Model Number.	ALTHEA06W
Product weight (kg).	0.0445
Dimensions (W x D x H).	40 x 29 x 42.5 mm
Product Height.	42.5 millimeter
Product Width.	40 millimeter
Product Depth.	29 millimeter
Product Net Weight.	44.5 kilogram
Power input.	AC 100.0-240.0V, 50/60Hz, 0.5A max

