

ALTHEA14W 20W 1-Port USB-C PD Charger, PD 3.0

Product Images





Short Description

- **Dedicated Port Connector:** Equipped with a USB-C ports (with PD 3.0), providing up to 20W of total power and high-speed charging for a wide range of devices with varying power requirement.
- **Wide Compatibility:** Supports a range of output options from 5.0V to 12.0V across its ports, ensuring compatibility with devices from smartphones to laptops.
- **Enhanced Safety Features:** Built-in protections against overload, short circuiting, and overheating, ensuring the safety of both the charger and connected devices.
- **Efficiency and Fast Charging Technology:** Incorporates USB Power Delivery (PD) 3.0 technology for efficient and rapid charging, ensuring broad device compatibility.

Description

This charger features a dedicated USB-C port with USB Power Delivery (PD) 3.0, delivering up to 20W of total power for high-speed charging across a variety of devices. It supports a wide range of output options from 5.0V to 12.0V, ensuring compatibility with both smartphones and laptops. The charger is designed with enhanced safety features, including protections against overload, short circuiting, and overheating, to keep both the charger and connected devices safe. With USB Power Delivery (PD) 3.0 technology, it provides efficient and rapid charging, making it a versatile solution for diverse charging needs.

Additional Information

Number of cartons per pallet.	16 piece
Package Volume.	329.0496 cubic_centimeter
Pallet Net Depth.	800 millimeter
Pallet Net Width.	1200 millimeter
Pallet Net Height.	1800 millimeter
Power Plug Type.	EU
USB Power Delivery revision	3.0
Number of simultaneously connected devices (max).	1
Port 1 Power Output.	USB-C output: DC 5.0V/3.0A, 9.0V/2.22A, 12.0V/1.67A
Programmable power supply (PPS) (YES/NO).	No
USB Type-C ports quantity.	1
Fast charging technology.	Power Delivery 3.0
Number of outputs.	1
Housing Material.	Polycarbonate (PC)
Harmonized System (HS) code.	850440
Customs product code (TARIC).	8504408390
Quantity per Pallet.	1600 piece
Input current.	0.6 ampere
Maximum AC Input.	240 volt
Minimum AC Input.	100 volt
Maximum power.	20 watt
Power Protection Features.	Over current, Over power, Short circuit
Sustainability Compliance.	No
Operating temperature (T-T) Max.	40 celsius

Operating temperature (T-T) Min.	0 celsius
Storage relative humidity (H-H) Max.	90%
Storage relative humidity (H-H) Min.	5%
Operating relative humidity (H-H) Max.	95%
Operating relative humidity (H-H) Min.	5%
Storage temperature (T-T) Max.	80 celsius
Storage temperature (T-T) Min.	-20 celsius
Quantity per Pack.	1 piece
Package Depth.	164 millimeter
Package Height.	33 millimeter
Package Width.	60.8 millimeter
Product Gross Weight.	10 gram
Approval and Compliance.	CE, ERP, ROHS, REACH
Package Content.	Quick installation guide
Operating humidity.	5% RH ~ 95% RH
Operating temperature.	0°C ~ 40°C
Storage temperature.	-20°C ~ 80°C
Package Contents.	ALTHEA14W Multilingual quick installation guide
Color.	White
EAN.	4015867236451
Model Number.	ALTHEA14W
Product weight (kg).	0.052
Dimensions (W x D x H).	42.3 x 28 x 40.8 mm
Product Height.	40.8 millimeter
Product Width.	42.3 millimeter
Product Depth.	28 millimeter
Product Net Weight.	52 gram

Power input.

AC 100.0-240.0V, 0.6A max, 50-60Hz

