


351003 80mm Thermal POS Receipt Printer with Auto Cutter,USB/Ethernet/Serial/Cash Drawer connection

Product Images





Short Description

- Wide compatibility with most types of business software
- High-speed, stable with low-noise printing
- Easy paper loading system
- Compatible with POS/ESC command set
- Thermal printing, no need for ink ribbon and toner
- Work with standard 80mm thermal paper

Description

The equip® POS range offers reliable equipment to suit a wide variety of Point of Sale (POS) situations and business needs. The solutions are designed for retail, service-type businesses or the food and beverage industry.

The equip® Thermal POS Receipt Printers are perfect for situations such as customer checkout and food and beverage operations. The printer is compatible with ESC/POS printing commands and offers high-speed, stable printing and auto-cutter functionality.

Additional Information

Harmonized System (HS) code.	844332
Customs product code (TARIC).	8443321000
Point x mm (dot).	8dots/mm
Print Resolution (dpi).	203dpi
Printing Speed (mm/s).	150mm/s
POS Programming Language.	ESC/POS
RFID Support.	Yes
Supported Barcode Type.	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128/QR CODE
Badge printing.	No
Color Badge Printing.	No
Double-side badge printing.	No
Film Stripper.	No
Maximum print width.	72mm
Rewinder.	No
Shell material.	ABS+PC
Approval and Compliance.	CE , RoHS
Operating humidity.	20% RH ~ 80% RH
Operating temperature.	-10°C ~ 50°C
Compatible operating systems.	Windows 7/8/10/11 UBUNTU 12.04 32/64 UBUNTU 14.04 32/64 Linux Android Mac OS 11.1 or above
Package Contents.	80mm Thermal POS Receipt Printer x 1 Power adapter x 1 USB cable x 1 Thermal paper roll x 1 Resource CD x 1 Quick installation guide x 1
Color.	Black
EAN.	4015867229088
Model Number.	351003
Dimensions (W x D x H).	195 x 145 x 143.3 mm

Product weight (kg).	1.04
On/Off switch	Power On/Off
Wireless connection.	No
Printheads lifespan.	100km
Magnetic stripe encoder.	No
Power input.	Power Adapter + Power Cord, 100-240V/AC,50-60Hz
Power Output.	Cash Drawer Control: DC 24V
Power supply.	24V / 1.5A

