

		
Picture		
Model	Trackmix Series G770	
Video & Audio	Image Sensor	1/3" + 1/2.7" CMOS Sensor
	Video Resolution	UP To: 3840 x 2160 (8.0 Megapixels) at 15 frames/sec
	Lens	f=2.8mm@F=1.6, f=8mm@F=1.6
	Video Format	H.264,H.265
	Field of View	Horizontal: 108°-57° Vertical: 38°-21°
	Zoom Mode	6X hybrid zoom
	Day & Night	IR-cut filter with auto-switching
	Infrared Night Vision	Up to 30 Meters (90ft)(LED: 2pcs/850nm)
	Color Night Vision	Spotlight: 1pcs/6500K/450 Lumens
	Frame Rate	Main Stream: 10fps - 15fps(Default: 15fps) Sub Stream: 10fps - 15fps
	Code Rate	Main Stream: 1024Kbps - 4096Kbps(Default: 3072Kbps) Sub Stream: 64Kbps - 672Kbps
	Audio	Two-way Audio
Power Requirements	Battery	7.2V,5100mAh (36.72Wh) rechargeable battery (Battery life varies based on settings, usage & temperature)
	Solar	Reolink Solar Panel 2
	DC Power	5V/2A
Interface	Power Power	USB Type-C port
	Reset Button	Yes
	SD Card Slot	MicroSD card slot (Max. 128GB)
	SIM Card Slot	Nano SIM card slot
	Audio In/Out	Built-in Microphone and Speaker
Pan&Tilt	Pan &Tilt	Pan: 355°, Tilt: 0°~90°; (PT speed is configurable)
	Preset Points	Suppots 1 guard position & up to 32 preset positions
	Auto-Tracking	Support
3G/4G	Frequency Bands	Europe: LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8
		America: LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71
		Australia: LTE FDD: B1/B3/B5/B7/B8/B28 WCDMA: B1/B5/B8
Software	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P
	User Access	Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
Other Features	Smart Alarm	PIR Detection/Human Detection/Vehicle Detection/Animal Detection
	PIR Detecting Distance	Adjustable, up to 11m (33ft)
	PIR Detecting Angle	100° horizontal
	Record Mode	Motion Triggered Recording
	Time Lapse	Yes
	Smart Home Compatibility	Google Assistant
	Cloud Storage	Supports Reolink Cloud (available in selected countries)
Working Environment	Temperature	Operating Temperature: -10°C~+55°C (14°F~131°F)
	Humidity	Operating Humidity: 20% ~ 85%
	Weatherproof	IP65
Mechanical	Dimension	228.2*147*129mm
	Weight	1.4KG
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/