

Picture



Model

E Series E560

Video & Audio

Image Sensor

1/2.8" CMOS Sensor

Video Resolution

3840X2160(8Megapixels)@20FPS

Lens

f=2.8-8mm Max: F1.6

Zoom

3X

Video Format

H.265(More than 5MP) Other H.264

Field of View

Horizontal: 94° ~ 50°

Vertical: 53° ~ 30°

Day & Night

IR-cut filter with auto-switching

Infrared Night Vision

Up to 12 Meters (40ft); LED: 10pcs/1.4W/850nm

Color Night Vision

4pcs/3.3W/6500K/180Lumens

Audio

Two-way Audio

Power

DC Power

DC 12.0V=1A, <12W

Power

DC power port

Interface

System

Reset Button

Ethernet

One 10M/100Mbps RJ45

Storage

MicroSD card slot (Max. 256GB)

Audio

Built-in Microphone and Speaker

Pan&Tilt

Pan &Tilt Range

Pan: 355°, Tilt: 0°~50°

Auto Tracking

Support

Wi-Fi

Wireless Standard

IEEE 802.11a/ac/ax/ b/g/n

Operating Frequency

2.4 GHz/5 GHz

Wireless Security

WPA/WPA2/WPA3

Software Features

Frame Rate

Main Stream: 2fps - 20fps(default: 20fps)

Sub Stream: 4fps - 15fps(default: 10fps)

Code Rate

Main Stream: 2048Kbps - 5120Kbps(default: 4096Kbps)

Sub Stream: 64Kbps - 512Kbps(default: 256Kbps)

Browser Supported

Edge, Chrome, Firefox, Safari

OS Supported

PC: Windows, Mac OS; Smartphone: iOS, Android

Smart Alarm

Motion detection/Human Detection/Vehicle Detection/Pet Detection

Record Mode

Motion Record/Schedule Record (Default: Motion Record)

Protocols & Standards

HTTPS, SSL, TCP/IP, UDP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP,

Maximal User Access

Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)

20 Users (1 admin account & 19 user accounts);

Work with

Google Assistant, Reolink NVR

Working Environment

Temperature

Operating Temperature: -10°C~+50°C (14°F~122°F)

Humidity

Operating Humidity: 10% ~ 90%

Waterproof

IP65

Size & Weight

Dimension

Φ90 x 120mm

Weight

458g

Warranty

Limited Warranty

2-year limited warranty. For support, visit <https://support.reolink.com/hc/en-us/>